

10/100 VDSL2 Ethernet Extender Kit over Single Pair Wire – 1km

ID del Producto: 110VDSLEXTGB



The 110VDSLEXTGB VDSL Ethernet extender kit allows you to span a 10/100 network over extremely long distances (up to 1km) while still maintaining high-speed network connectivity. The device allows you to run the connection over standard RJ45 cabling, existing RJ11 phone lines, or any other set of single pair wires. The VDSL (VDSL2) kit is simple to install and provides an out-of-the-box solution as both the Ethernet-VDSL extender and receiver units are included.

A perfect solution for a broad range of applications including connecting isolated user stations within the same building or between separate buildings, or overcoming infrastructure obstacles and distances (e.g. older stone/concrete architecture) where new wiring or wireless may be impossible. The VDSL Ethernet LAN Extender kit helps to eliminate expense by allowing video streaming and data to share the same telephone pair without interference.

The 110VDSLEXT requires only a single pair of wires to function, while offering the ability to use multiple sets of the devices to create several simultaneous connections to your remote building. In these multiple set configurations, you have the ability to use up to 4 sets over a single Cat5e or Cat6 cable which can be used as separate LAN (or VLAN) connections, or bridged into a trunk line for additional speed/bandwidth over long distances (up to two sets only over standard Cat5).

Solution Diagrams:

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certificaciones, Reportes y Compatibilidad



Aplicaciones

- Provide ethernet over copper connectivity to a user or network segment that is in an isolated area of a large complex or in another building altogether
- Extend network connectivity to remote areas of stadiums, auditoriums or other venues
- Industrial applications include controlling CNC machinery, polling bar code scanner data, administering process control equipment, and other harsh environment applications
- Monitor and control medical equipment, security keypads/card scanners, point of sale equipment and remote sensor data, and various other healthcare related network communications
- Remote sensor monitoring for traffic flow management (air traffic control, expressway flow)

Características

- IEEE 802.1Q VLAN tag transparent
- Selectable CPE and CO mode via DIP switch
- Supports flow control for Fast Ethernet (pause frame or Back Pressure)
- Allows you the ability to select fixed SNR margin (9 dB) or fixed target data rate
- Light in weight and a very compact design
- Supports both symmetric and asymmetric transmission

Hardware

Política de Garantía	2 Years
Estándares Industriales	IEEE 802.3/802.3u/802.3x10/100 Base-T Auto-Negotiation, Auto-MDI/MDI-X
	On-board surge protection
	VDLS2 ITU-T G.993.2, VDLS ITU-T G.993.1, and VDLS2/VDLS ITU-T G.997.1 compliant

Rendimiento

Tasa de Transferencia de Datos Máxima	0m - 100Mbit/s
	300m - 75Mbit/s
	1km - 10Mbit/s

	Distancia Máxima	1 km (0.6 mi)
Conector(es)	Conectores de la Unidad Local	2 - RJ-45
	Conectores de Unidad Remota	2 - RJ-45
Observaciones / Requisitos	Nota	You have the ability to use up to four sets over a single Cat5e or Cat6 cable which can be used as separate LAN (or VLAN) connections, or bridged into a trunk line for additional speed/bandwidth over long distances (Up to two sets only over standard Cat5).
Indicadores	Indicadores LED	3 - LAN: ACT/LNK, 10/100 Mbps, Half/Full Duplex
		3 - VDSL: Power On/Off, CO/CPE, Idle/Trained/Link
Requisitos de Energía	Adaptador de Corriente Incluido	2 adaptadores de CA (corriente alterna) incluidos
	Tensión de Entrada	230 AC
	Tensión de Salida	12V DC
	Alimentación de Salida	1A
	Polaridad Central	Positivo
	Tipo de Enchufe	M
	Consumo de Energía	12
Requisitos Ambientales	Temperatura Operativa	0°C to 50°C (32°F to 122°F)
	Temperatura de Almacenamiento	0°C to 70°C (32°F to 158°F)

Humedad 10~90% RH

Características
Físicas

Color	Negro
Longitud del Producto	3.7 in [9.5 cm]
Ancho del Producto	2.8 in [7.2 cm]
Altura del Producto	0.9 in [2.2 cm]
Peso del Producto	3.2 oz [90.0 g]

Información de la
Caja

Cantidad de Paquetes	1
Longitud de la Caja	5.4 in [13.7 cm]
Ancho de la Caja	5.8 in [14.8 cm]
Altura de la Caja	3.7 in [9.5 cm]
Peso (de la Caja) del Envío	2.1 lb [0.9 kg]

Contenido de la
Caja

Incluido en la Caja	1 - Extender
	1 - Receiver
	2 - RJ-45 to VDSL Cable
	2 - Power Adapter
	1 - Instruction Manual

* La apariencia y las especificaciones del producto están sujetas a cambios sin previo aviso.