

2-Port PCI Express Serial Card, Dual Port PCIe to RS232 (DB9) Serial Card, 16C1050 UART, Standard or Low Profile Brackets, COM Retention, For Windows & Linux

Product ID: 21050-PC-SERIAL-CARD



Add serial communication support to your desktop computer or Small Form Factor (SFF) system, using this two-port serial card. RS-232 (DB9) support enables control and communication with a serial peripheral device.

Install this card to enable the continued use of legacy serial devices, preventing down time and avoiding costly upgrades. The 2-port PCIe serial card is ideal for system upgrades in a wide range of applications for logistics, manufacturing, and freight sectors, and the IT industry, such as POS equipment, security systems, A/V installations, and more.

The RS-232 card features dual ports with 16C1050 UART support, 256-byte FIFO (transmit/receive), bi-directional speeds up to 921.6 Kbps per port, low-profile brackets are included for SFF systems, and serial port LED status lights. In addition, it supports Windows and Linux systems for maximum compatibility.

21050-PC-SERIAL-CARD is backed for 2-years by StarTech.com, including free lifetime 24/5 multi-lingual technical assistance.

Certifications, Reports and Compatibility



























Applications



Features

- PCIE TO SERIAL: Connect serial RS232 (DB9) devices to a computer with this PC serial card. Features support for high performance 16C1050 UART on both DB9 male ports. Monitor activity with the built-in LED status lights on the PCI express DB9 card
- DEVICE COMPATIBILITY: Use this serial interface card to connect barcode readers/scanners, receipt printers, scales, PLCs, medical devices, etc. The UART PCIe card supplies 5V or 12V power over pin 9. Low-profile brackets are included
- APPLICATIONS: This card is ideal for IT applications such as server rooms, industrial control/automation, logistics, and laboratories. Continue using legacy hardware with this RS232 PCIe card. DB9 ports accept screw locking serial cables
- DUAL SERIAL PORT CARD SPECS: 16C1050 UART Max Baud 921.6 Kbps per Port 256 Byte FIFO COM Retention Supports Windows and Linux Asix AX99100 Chipset Odd/Even/Mark/Space/None Parity Modes 5/6/7/8/9 Data Bits PCIe 2.0 x1 Low-profile Brackets
- THE IT PRO'S CHOICE: Designed and built for IT Professionals, this PCIe to RS232 card is backed for 2-years, including free lifetime 24/5 multi-lingual technical assistance

Hardware		
	Warranty	2 Years
	Ports	2
	Interface	Serial
	Bus Type	PCI Express
	Card Type	Standard Profile (LP bracket incl.)
	Port Style	Integrated on Card
	Industry Standards	PCI Express Version 2.0 x1
	Chipset ID	ASIX - AX99100
		ASIX - ZT3243LFEY
Performance		
	Serial Protocol	RS-232
	Max Baud Rate	921.6 Kbps
	Data Bits	5, 6, 7, 8, 9
	FIFO	256 Bytes



	Flow Control	Hardware and Software
	Parity	Even, Odd, None, Space, and Mark
Connector(s)	Compostor Type(s)	4. DOLEVINGO VA
	Connector Type(s)	1 - PCI Express x1
	External Ports	2 - DB-9 (9 pin, D-Sub) Male
Software		
	OS Compatibility	Windows 7, 8, 8.1, 10, 11
		Windows Server 2016, 2019
		Linux 2.6.13 and newer. LTS Versions Only
Special Notes / Requirements		
	System and Cable Requirements	Computer with an available PCI Express x1 or greater slot
Indicators		
	LED Indicators	2 - Green = Activity
		Off = No Activity
Environmental		
	Operating Temperature	0C to 55C (32F to 131F)
	Storage Temperature	-40C to 75C (-40F to 167F)
	Humidity	5 ~ 95% RH
Physical Characteristics		
	Color	Yellow
	Material	Steel
	Product Length	0.7 in [1.8 cm]
	Product Width	2.9 in [7.3 cm]
	Product Height	4.7 in [12.0 cm]
	Weight of Product	1.8 oz [51.0 g]



Packaging Information

Package Quantity 1

Package Length 5.7 in [14.4 cm]

Package Width 8.1 in [20.7 cm]

Package Height 1.5 in [3.8 cm]

Shipping (Package) Weight

5.3 oz [151.0 g]

What's in the Box

1 - Two-port PCIe Serial Card Included in Package

2 - Low Profile Bracket

1 - Quick-start Guide

^{*}Product appearance and specifications are subject to change without notice.