

USB C Multiport Video Adapter with HDMI, VGA, Mini DisplayPort or DVI - USB Type C Monitor Adapter to HDMI 1.4 or mDP 1.2 (4K) - VGA or DVI (1080p) - Space Gray Aluminum

Product ID: CDPVDHMDPSG



This spacegray USB-C multiportvideoadapteroffers a portable solution for connecting your USB Type-Claptop to a VGA, DVI, HDMI or Mini DisplayPort display. The adapter is also available in [%product id="CDPVGDVHMDMP" text="silver (CDPVGDVHMDMP)"] and [%product id="CDPVDHMDPRG" text="rose gold (CDPVDHMDPRG)"].

Avoid the hassle of carrying different adapters for different displays with this 4-in-1USB-C adapter. With VGA, DVI, HDMI andmDPoutput, you can connect your laptop to virtually any display, a convenient plug-and-play solution for travel or Bring Your Own Device (BYOD) applications.

The HDMI andmDPoutputs on this USB-C video adapter support UHD 4K resolutions, providing four times the picture quality of high-definition 1080p.All ofthe outputs (HDMI,mDP, VGA, DVI) can support high-definition resolutions of up to 1920 x 1200.

The USB Type-C adapter has an aluminum housing designed to match yourspace gray MacBook and is compatible with any device that supports USB-C DP Alt Mode. Featuring a built-in USB-C cable with magnetic cable manager, the USB-C video adapter conveniently stores away for easy travel.

The CDPVDHMDPSG is backed by a StarTech.com 3-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Connect to virtually any display while traveling

- Connect your BYOD MacBook to a VGA, DVI, HDMI or mDP display at work or school
- Connect a secondary VGA, DVI, HDMI or mDP monitor to your MacBook

Features

- **4-IN-1 MULTIPORT USB-C VIDEO ADAPTER:** USB-C DP Alt Mode to any one of HDMI 1.4 (4K 30Hz & 7.1ch audio), mDP 1.2 (4K 60Hz & 2ch audio), VGA or DVI (1080p), HDCP 2.2/1.4, Thunderbolt 3 compatible
- **TOUGH & PORTABLE:** Durable aluminum Space Gray enclosure with a magnetically-secured hideaway cable wrap for on-the-go users in the office, at home, boardrooms, and classrooms
- **COMPATIBILITY:** USB-C display adapter for Dell XPS/Precision/Latitude, Lenovo ThinkPad X1 Carbon/Extreme, Surface Laptop 3/Surface Book 3, TB3 MacBook Pro/Air, HP EliteBook/Spectre/ZBook, Chromebooks
- **TESTED & VERIFIED:** USB Type-C adapter tested @ 4K mini DisplayPort (60Hz)/HDMI (30Hz) or 1080p VGA/DVI with TV, monitor & projector brands like Dell, Asus, Acer, LG, Samsung, Sharp, Sony, Epson
- **EASY TO USE:** Supporting a driverless plug-and-play setup, this adapter is fully compatible with multiple OS platforms: Windows / macOS / Linux / Chrome OS

Hardware	Warranty	3 Years
	Active or Passive Adapter	Active
	AV Input	USB-C
	AV Output	HDMI - 1.4
	AV Output	DVI-I (Digital Only) - Single-Link
	AV Output	VGA
	AV Output	Mini DisplayPort - 1.2
	Chipset ID	Cypress - CYPD1120
		Cypress - CY7C65210
		Parade - PS8348B
	Parade - PS171	
Performance	Maximum Cable Distance To Display	49.9 ft [15.2 m]
		49.9 ft [15.2 m]
	Maximum Cable Distance To Display	49.9 ft [15.2 m]
	Maximum Cable Distance To Display	DisplayPort 1.2
	Video Revision	1920 x 1200 @ 60Hz
		3840 x 2160 @ 30Hz
	Maximum Analog Resolutions	Max HDMI output: 3840 x 2160 @ 30Hz
	Maximum Digital Resolutions	Max mDP output: 3840 x 2160 @ 60Hz
	Supported Resolutions	
	Wide Screen Supported	

Audio Specifications	HDMI and mDP output: 3840 x 2160, 2560 x 1600, 1920 x 1200, 1920 x 1080, 1280 x 720
Audio Specifications	
Audio Specifications	DVI and VGA output: 1920 x 1200, 1920 x 1080, 1280 x 720
Audio Specifications	Yes
MTBF	HDMI - 7.1 Channel Audio
	DVI - No Audio Support
	VGA - No Audio Support
	Mini DisplayPort - 2 Channel Audio
	654,111 hours

Connector(s)	Connector A	USB-C (24 pin) DisplayPort Alt Mode
	Connector B	Mini-DisplayPort (20 pin)
	Connector B	VGA (15 pin, High Density D-Sub)
	Connector B	DVI-D (25 pin)
	Connector B	HDMI (19 pin)

Special Notes / Requirements	Note	Only one video output is supported on the video adapter at a time, if multiple connections are made, only one of the outputs will function
	Note	Maximum Cable Distance to Display refers to digital video. VGA distance capabilities are dependent upon the quality of your cabling

Environmental	Operating Temperature	0C to 45C (32F to 113F)
	Storage Temperature	-10C to 70C (14F to 158F)
	Humidity	Storage: 5% ~ 90 % RH (no condensation) Operating: 10% ~ 85 % RH (no condensation)

Physical Characteristics	Color	Space Gray
	Material	Aluminum
	Cable Length	4.3 in [1.1 cm]
	Product Length	6.9 in [1.8 cm]
	Product Width	5.7 in [1.4 cm]
	Product Height	1.2 in [30.000 mm]
	Weight of Product	6.4 oz [180.000 g]

Packaging Information	Package Length	2.2 in [55.000 mm]
	Package Width	4.1 in [1.0 cm]
	Package Height	0.6 in [16.000 mm]
	Shipping (Package) Weight	4.3 oz [121.000 g]

What's in the Box	Included in Package	travel A/V adapter
--------------------------	---------------------	--------------------

****Product appearance and specifications are subject to change without notice.***

