

Cisco GLC-T Compatible SFP Module (10 Pack) - 1000BASE-T - SFP to RJ45 Cat6/Cat5e - 1GE Gigabit Ethernet SFP - RJ-45 100m - Cisco Firepower, ASR920, IE2000

Product ID: GLCT10PKST



The GLCT10PKST is a ten-pack of our Cisco GLC-T compatible copper transceiver module that has been designed, programmed and tested to work with Cisco brand switches and routers. It delivers dependable 1 GbE connectivity over copper cable, for 1000BASE-T compliant networks, with a maximum distance of up to 100 m (328 ft).

- 1000 Mbps
- Copper
- RJ45 Connector
- 100 m (328 ft)
- 4,655,371 hours
- Less than 1.3 Watts
- No

This SFP copper module is hot-swappable, making upgrades and replacements seamless by minimizing network disruptions.

All StarTech.com SFP & SFP+ transceiver modules are backed by a lifetime warranty and free lifetime multilingual technical support. StarTech.com offers a wide variety of SFP modules and direct-attach SFP cables, providing the convenience and reliability you need to ensure dependable network performance.

Certifications, Reports and Compatibility



Applications

- Replacing defective or damaged SFP modules in Cisco switches and routers
- Expand your network to remote segments

Features

- 100% CISCO GLC-T COMPATIBLE: Works with Cisco switches like Firepower, ASR920, IE2000, IE4000,

ASR9000 and others

- **TECHNICAL SPECS:** 1000BASE-T 1 Gbps Copper RJ-45 Connector Distances up to 100m (328ft)
- **TESTED FOR OEM HOST COMPATIBILITY:** Hot-swappable in Cisco routers and switches
- **OUTSTANDING SUPPORT:** Backed by StarTech.com for the life of the module itself, not your equipment; our modules won't void your OEM support and with access to our Tech Advisors 5/24
- **WORKS WITH MSA COMPLIANT SWITCHES:** Also works with switch models from Ubiquiti, D-Link, Netgear, Supermicro, TP-Link and more that accept uncoded modules

Hardware	Warranty	Lifetime
	Compatible Brand	Cisco
	Industry Standards	IEEE 802.3ab 1000BASE-T
Performance	Maximum Data Transfer Rate	1000 Mbps 100 m (328 ft)
	Max Transfer Distance	Copper
	Type	No
	DDM	1000 Mbps (1 Gbps)
	Compatible Networks	4,655,371 hours
	MTBF	< 1.3 W
	Power Consumption (In Watts)	
Connector(s)	Local Unit Connectors	RJ-45
Special Notes / Requirements	Note	For use in 1 Gigabit networking equipment and media converters
Environmental	Operating Temperature	0C to 70C (32F to 158F)
	Storage Temperature	-40C to 85C (-40F to 185F)
	Humidity	30~75% RH
Physical Characteristics	Product Length	2.7 in [68.000 mm]
	Product Width	0.5 in [12.000 mm]
	Product Height	0.6 in [14.000 mm]
	Weight of Product	8.0 oz [227.000 g]
Packaging Information	Package Length	4.7 in [1.2 cm]
	Package Width	8.2 in [2.1 cm]
	Package Height	1.5 in [38.000 mm]

Shipping (Package) Weight	10.1 oz [286.000 g]
------------------------------	---------------------

What's in the Box	Included in Package	SFP transceivers
------------------------------	---------------------	------------------

****Product appearance and specifications are subject to change without notice.***

