

HDMI to RCA Converter Box with Audio

Product ID: HD2VID2



This HDMI to RCA converter box with audio converts a digital HDMI video source (with supporting audio) to work with analog RCA composite video televisions and displays, in both NTSC and PAL systems.

This HDMI to composite video converter provides features that ensure the highest quality output image, such as noise reduction, frame rate conversion and adaptive contrast enhancement.

With support for high-definition input resolutions up to 1080p, this RCA adapter letsyou convert your HDMI signal to composite video and audio while still producing a crystal-clear picture.

This lightweight composite adapter is compact and highly portable, so you can use it virtually anywhere. Offering support for a wide range of HDTV and PC input resolutions, this versatile RCA converter is a perfect solution for using newer devices with your existing legacy displays.

The ability to convert and use your new HDMlequipped device with your older televisions or displays not only offers flexibility but also saves you the cost of upgrading hardware, making it extremely convenient for home or office applications.

To ensure easy operation and installation, this unique RCA composite video converter allows for plug-and-play installation without any additional software or drivers.

HD2VID2 is backed by a 2-year StarTech.com warranty and free lifetime technical support.

Certifications, Reports and Compatibility











Applications



- Convert your HDMI signal to RCA composite video
- Continue to use standard definition displays with HDMI source devices
- Ideal for presentations that use dated projection systems
- Stream your new home videos onto your older TVs/displays

Features

- Convert your current HDMI source to composite video and audio (yellow, white and red outputs)
- Achieve HDTV resolutions with support for up to 1080p
- Support for multiple HDTV and PC input resolutions, compatible with almost any HDMI source device
- Hassle-free setup with simple plug-and-play installation
- Equipped with Overscan/Underscan functionality

Hardware	Warranty	2 Years
	Active or Passive Adapter	Active
	AV Input	HDMI
	AV Output	Composite
	AV Output	Audio RCA
	Audio	Yes
	Industry Standards	Standard HDMI, DVI 1.0
Performance	Supported Resolutions	Input
	Audio Specifications	TV - 1080p, 720p, 576p, 480p @ 60Hz
	MTBF	PC - 1920x1080, 1280x800, 1280x768, 1224x768, 800x600, 640x480 @ 60Hz
		Output
		480i, 576p
		Input - LPCM 2Ch, 48kHz
		Output - Stereo L/R
		1,301,084 hours
Connector(s)	Connector A	HDMI (19 pin)
	Connector B	Composite Video (1 x RCA)
	Input Connector(s)	Stereo Audio (2 x RCA)
Indicators	LED Indicators	Input LED
	LED Indicators	Power LED



Power	Power Source	AC Adapter Included
	Input Voltage	100 - 240 AC
	Input Current	0.4 A
	Output Voltage	5 DC
	Output Current	1000 mA
	Plug Type	M
Environmental	Operating Temperature	0C to 40C (32F to 104F)
	Storage Temperature	-20C to 60C (-4F to 140F)
	Humidity	20~90% RH
Physical Characteristics	Color	Black
	Product Length	4.3 in [1.1 cm]
	Product Width	3.9 in [100.000 mm]
	Product Height	1.0 in [25.000 mm]
	Weight of Product	10.1 oz [286.000 g]
Packaging Information	Package Length	8.3 in [2.1 cm]
	Package Width	5.9 in [1.5 cm]
	Package Height	2.0 in [52.000 mm]
	Shipping (Package) Weight	19.2 oz [545.000 g]
What's in the Box	Included in Package	HDMI to Composite Converter
	Included in Package	Universal Power Adapter (NA/JP, EU, UK, ANZ)
	Included in Package	User Manual
	Included in Package	Mounting Brackets
	Included in Package	Screws

^{*}Product appearance and specifications are subject to change without notice.