

Mini DisplayPort to HDMI Video Adapter Converter - White

Product ID: MDP2HDW



The MDP2HDW passive Mini DisplayPort to HDMI Video Adapter/Converter (White) offers a convenient HDMI/Mini-DisplayPort link, which enables you to connect an HDMI computer monitor or television to a device with a Mini-DisplayPort output (such as any Microsoft Surface Pro with mDP), while saving the expense of upgrading the monitor for compatibility.

The adapter supports high resolution output up to 1920x1200, offering a high quality solution for mirroring or extending a computer desktop onto a second display.

This versatile Mini DisplayPort to HDMI adapter requires a multimode DisplayPort port (DisplayPort ++) connection to function, and is compatible with Intel Thunderbolt output when connected directly to a supporting DisplayPort over Thunderbolt I/O port.

This adapter allows for audio pass-through if supported by the video source. Please review the video source manual to confirm support.

Backed by a StarTech.com 3-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Ideal for digital entertainment centers, home offices, business conference rooms and trade show displays
- Keep your existing HDMI monitor to be used with your new Mini-DisplayPort device
- Ideal for using your HDMI monitor as a secondary display

Features

- Easy to use passive cable, no software required
- Supports PC resolutions up to 1920x1200 and HDTV resolutions up to 1080p
- Compatible with Intel Thunderbolt

Hardware	Warranty	3 Years
	Active or Passive Adapter	Passive
	AV Input	Mini DisplayPort - 1.2
	AV Output	HDMI - 1.4
	Audio	Yes
	Industry Standards	DisplayPort 1.1a
	Chipset ID	HDMI 1.3a
		NXP - PTN3361
Performance	Maximum Cable Distance To Display	49.9 ft [15.2 m] 1920x1200 / 1080p
	Maximum Digital Resolutions	HDMI - 7.1 Channel Audio
	Audio Specifications	MDP2HDW hours
	MTBF	
Connector(s)	Connector A	Mini-DisplayPort (20 pin)
	Connector B	HDMI (19 pin)
Special Notes / Requirements	System and Cable Requirements	DP++ port (DisplayPort ++) required on video card or video source (DVI and HDMI pass-through must be supported)
Environmental	Operating Temperature	0C to 60C (32F to 140F)
	Storage Temperature	-10C to 70C (14F to 158F)
	Humidity	40~85% RH
Physical Characteristics	Color	White
	Cable Length	4.7 in [1.2 cm]
	Product Length	6.7 in [1.7 cm]
	Product Width	1.6 in [40 mm]
	Product Height	0.6 in [15 mm]

	Weight of Product	0.8 oz [24 g]
Packaging Information	Package Length	9.4 in [2.4 cm]
	Package Width	6.3 in [1.6 cm]
	Package Height	0.8 in [20 mm]
	Shipping (Package) Weight	1.8 oz [50 g]
What's in the Box	Included in Package	Mini-DisplayPort to HDMI converter

**Product appearance and specifications are subject to change without notice.*

