

6 ft Mini DisplayPort to VGA Adapter Converter Cable – mDP to VGA 1920x1200 - White

Product ID: MDP2VGAMM6W

Den MDP2VGAMM6W aktiva Mini DisplayPort till VGA-konverteringskabeln p 1,8m gr det mjligt att ansluta din Mini DisplayPort-utrustade enhet (som t.ex. en Macbook eller ngon Microsoft Surface Pro-enhet med mDP) direkt till en VGA-skrm eller -projektor utan extra adaptrar eller kablar - en kostnadseffektiv lsning fr att f din Mini DisplayPort-dator att fungera med en VGA-skrm eller-projektor. Kabeln har en elegant vit design som passar perfekt fr anslutning av Mac-datorer.

Kabeladaptern r kompatibel med Intel Thunderbolt vid anslutning direkt till en kompatibel DisplayPort ver Thunderbolt I/O-port. Eftersom konverterarkabeln stder videoupplsningar p upp till 1920x1200 kan du dessutom konvertera en DisplayPort-videoklla till VGA utan att frlora videokvalitet.

MDP2VGAMM6W tcks av StarTech.coms 3-rsgaranti och gratis livstidsgaranti p teknisk support.

Certifications, Reports and Compatibility



Applications

- Use your VGA monitor as a secondary display, connected to a Mini DisplayPort output
- Connect a Mini DisplayPort computer to a VGA projector for presentations or meetings in a boardroom or auditorium setting
- Connect your existing VGA display device (monitor, projector) to a DisplayPort output device (PC, laptop, Mac, Ultrabook)

Features

- Active Mini DisplayPort to VGA conversion
- Plug-and-Play Installation
- Supports resolutions up to 1920x1200 (WUXGA) and HDTV resolutions up to 1080p
- Compatible with Intel Thunderbolt devices that are capable of outputting a DisplayPort signal

| | | |
|------------------|---------------------------|----------------------------|
| Hrdvara | Warranty | 3 Years |
| | Active or Passive Adapter | Active |
| | AV-ingng | Mini DisplayPort - 1.2 |
| | AV-utgng | VGA |
| | Audio | No |
| | Chipset-ID | Analogix - 9832 |
| Prestanda | Maximal kabellngd | 6.0 ft [1.8 m] |
| | Maximal analog | 1920x1200 / 1080p (Output) |

| | |
|----------------------------|---------------------------|
| upplösning | 1920x1200 / 1080p (Input) |
| Maximal digital upplösning | VGA - No Audio Support |
| Audio-specifikationer | |

| | | |
|--------------------|-------------|----------------------------------|
| Kontakt(er) | Connector A | Mini-DisplayPort (20 pin) |
| | Connector B | VGA (15 pin, High Density D-Sub) |

| | | |
|-------------|---------------------|---------------------------|
| Milj | Drifttemperatur | 0C to 60C (32F to 140F) |
| | Frvaringstemperatur | -10C to 70C (14F to 158F) |
| | Luftfuktighet | 40%-85%RH |

| | | |
|-----------------|--------------|------------------|
| Utseende | Frg | White |
| | Kabellngd | 6.0 ft [1.8 m] |
| | Produktlängd | 36.0 in [9.2 cm] |
| | Produktbredd | 1.6 in [40 mm] |
| | Produktthjd | 0.6 in [15 mm] |
| | Produktvikt | 3.3 oz [94.6 g] |

| | | |
|-------------------|------------------------|-----------------|
| Frpäckning | Package Length | 8.8 in [2.2 cm] |
| | Package Width | 7.8 in [2.0 cm] |
| | Package Height | 0.6 in [15 mm] |
| | Fraktvikt (frpackning) | 4.2 oz [120 g] |

| | | |
|-------------------------|----------------|---------------------------------------|
| Vad det r i ldan | Ingr i paketet | Mini DisplayPort to VGA Adapter Cable |
|-------------------------|----------------|---------------------------------------|

**Product appearance and specifications are subject to change without notice.*

