

1-Port 2.5GbE M.2 2280 Network Card, Multi-Gigabit Speeds (2.5G/1G/100M/10M), NBASE-T (802.3bz) NIC, M.2 B+M Key, PCIe Ethernet Interface, For SFF/Desktop PCs

Product ID: MR12GI-NETWORK-CARD



This 2.5 GbE M.2 Network Interface Card (NIC) features an Intel I225-V chipset with Intel vPro technology, for enhanced performance and data integrity. Variable multispeed options (2.5/1Gbps and 100/10Mbps) enable support of new and legacy network hardware. Leverage existing Cat5e or CAT6 cabling infrastructure while adding 2.5GBASE-T (802.3bz) compatibility for seamless integration.

The PCIe network card takes advantage of Intel vPro technology for remote management and troubleshooting capabilities. Improve bandwidth for data-intensive applications, network sharing, FTPs, online or local storage/backup, and online content streaming or uploading while reducing network slowdowns. Access up to 2.5GBASE-T speeds using Cat5e (or better) cabling, to maximize existing networks and equipment.

The network adapter card connects to an available M.2 2280 PCIe slot (B or M key compatible). Standard and low-profile brackets and a 2ft (60cm) Cat6 adapter cable are included for versatile installation. Compatible with Windows, VMware, and Linux.

This Ethernet card supports the following advanced features: PXE Boot, Wake-on-Lan (WoL), VLAN tagging, 9K jumbo frame, half-duplex, auto-negotiation, and Error Correcting Memory (ECC) for optimal network functionality.

Windows' 11 Windows' 10 Windows' Server 2019

Certifications, Reports and Compatibility

STARTECH.COM



Applications

Features

• 1-PORT 2.5GbE M.2 NETWORK CARD: High-performance M.2 Ethernet 2.5Gbps network card with Intel I225-V-chip; Multi-gigabit; Leverage existing Cat5e/Cat6 cabling (or better); NBASE-T (802.3bz); PCI Express M2 2280 B or M key compatible

• M.2 INTERFACE: M.2 2280 form factor is ideal for upgrading systems that do not have PCIe expansion slots or where slots are already in use; Includes 2ft (60cm) M/F Cat6 cable adapter for running Ethernet port to full/low-profile bracket on the rear of the PC

• COMPATIBILITY: 2.5GBASE-T variable speed options (2.5/1Gbps and 100/10Mbps) with auto-negotiation; Supports B or M key M.2 PCIe Gen 2 slots; Network interface card for PC is compatible with Windows/VMware/Linux; Full and low profile bracket included

• IT MANAGEMENT: Intel vPro for remote management and troubleshooting; PXE boot enabled for faster deployment/updates; 9K jumbo frame for reduced packet overhead; Remotely boot a system using WoL; VLAN support for efficient network management

• THE IT PRO'S CHOICE: Designed and built for IT Professionals, this 2.5 GbE M.2 NIC is backed for two years, including free lifetime 24/5 multi-lingual technical assistance

| Hardware | Warranty | 2 Years |
|-------------|-------------------------------|---|
| | Ports | 1 |
| | Interface | RJ45 (2.5G Ethernet) |
| | | M.2 PCIe |
| | Bus Type | M.2 |
| | Card Type | Standard Profile (LP bracket incl.) |
| | Industry Standards | IEEE 802.3bz (2.5GBASE-T) br/>IEEE 802.3ab (1000BASE-T) br/>IEEE 802.3u (100BASE-TX) br/>IEEE 802.3i (10BASE-TX) br/>IEEE 802.1Q (VLAN) br/>IEEE 802.1p (QoS) br/>IEEE 802.1AS (AVB) br/>IEEE P802.3az (EEE) br/>IEEE 1588 (PTP) PCI Express Version 2.0 |
| | Chipset ID | Intel - I225-V |
| Performance | | |
| | Maximum Data Transfer Rate | 2.5Gbps |
| | Compatible Networks | 2.5G/1G/100Mbps/10Mbps |



| | Auto MDIX | Yes |
|-----------------------------|---------------------|---|
| | PXE | Yes |
| | Full Duplex Support | Yes |
| | Jumbo Frame Support | 9K max. |
| | Promiscuous Mode | Yes |
| Connector(s) | Connector Type(s) | 1 - M.2 (B+M-Key, PCle) |
| | External Ports | 1 - RJ-45 |
| Software | OS Compatibility | Windows 10, 11 br/>Windows Server 2019, 2022 Linux 5.8.x and up - LTS Versions only VMware ESXi 7.0 |
| Indicators | LED Indicators | 1 - Left LED Indicator is Link Status Solid Green: Active Link Flashing Green: Activity |
| | | 1 - Right LED Indicator is Link Speed Solid Green: 2.5 Gbps Solid Amber: 1.0 Gbps Off: 100 or 10 Mbps |
| Power | Power Source | Bus Powered |
| Physical Characteristics | | |
| ondracteristics | Color | Red |
| | Form Factor | Separate Cable |
| | Product Length | 0.9 in [2.2 cm] |
| | Product Width | 3.1 in [8.0 cm] |
| | Product Height | 0.6 in [1.5 cm] |
| | Weight of Product | 0.5 oz [15.0 g] |
| Packaging Information | Package Length | 6.7 in [17.0 cm] |





| | Package Width | 5.6 in [14.2 cm] |
|-------------------|------------------------------|--------------------------|
| | Package Height | 1.2 in [3.0 cm] |
| | Shipping (Package) Weight | 4.9 oz [140.0 g] |
| What's in the Box | | |
| | Included in Package | 1 - M.2 Network Card |
| | | 1 - CAT6 Cable Adapter |
| | | 1 - Full-Profile Bracket |
| | | 1 - Low-Profile Bracket |
| | | 1 - M3x2 Screw |
| | | 1 - Quick-Start Guide |

*Product appearance and specifications are subject to change without notice.

