


4-Port USB 3.1 PCIe Card - 3x USB-A and 1x USB-C - 2x Dedicated Channels

Product ID: PEXUS313AC2V



This USB 3.1 PCIe card lets you add three USB Type-A ports and one USB Type-C port to your computer, through a PCI Express slot. It makes it easy to upgrade your PC to the faster speed of USB 3.1 (10Gbps) so that you can access newer peripherals at twice the speed of traditional USB 3.0 (5Gbps) cards.

When multiple devices are connected, traditional single-bus USB cards share the maximum bandwidth between all ports. By employing two host controller chipsets, shared across two ports rather than four, this 4-port PCIe to USB 3.1 card dedicates up to 10Gbps for each set of two USB ports. It reduces performance bottlenecks and doubles your total available bandwidth to 20Gbps.

With higher data throughput support, the card is ideal for external hard drives, hard drive enclosures, and large external storage devices. It lets you access multiple devices simultaneously for read and write access.

The 4-port USB 3.1 controller card adds dual independent channels to your computer and shares 10Gbps of bandwidth between two USB ports.

Each set of two ports shares a combined bandwidth of 10Gbps. If a single device is accessing the channel, the card will provide data transfer rates of up to 10Gbps to the device. If two devices are accessing the channel simultaneously, the 10Gbps of bandwidth will be shared between both devices.

The PEXUS313AC2V is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Upgrade an older PCIe equipped desktop from USB 3.0/2.0 to USB 3.1 Gen 2 (10Gbps)
- Expand the USB capabilities of your system with four additional USB ports, or add the card to a new PC build
- Ideal for file backups, video editing, and data recovery, using high-bandwidth USB 3.1 Gen 2 external storage solutions

Features

- Add three USB-A and one USB-C external USB 3.1 ports on two independent bus channels
- Transfer files and access USB 3.1 devices faster, with up to 10Gbps throughput
- Connect large external storage solutions: optional LP4 or SATA power connector provides up to 900mA per USB port
- Add room for more devices on your current system
- Compatible with older USB 3.0 and USB 2.0 devices

Hardware	Warranty	2 Years
	Ports	4
	Interface	USB 3.1 Gen 2
	Bus Type	PCI Express
	Card Type	Standard Profile
	Port Style	Integrated on Card
	Industry Standards	USB 3.1 Specification Rev. 1.0
	Chipset ID	USB Specification Rev. 2.0 PCI Express Base Specification Rev. 2.0 Intel xHCI Specification Rev. 1.1 UASP (USB Attached SCSI Protocol) Rev. 1.0 ASMedia - ASM1142</br>Pericom PI7C9X2G308GP
	Performance	Maximum Data Transfer Rate
Type and Rate		USB 3.1 Gen 2 - 10 Gbit/s
UASP Support		Yes
Connector(s)	Connector Type(s)	PCI Express x4
	Internal Ports	LP4 (4 pin; Large Drive Power)
	Internal Ports	SATA Power (15 pin)
	External Ports	USB 3.1 USB Type-A (9 pin, Gen 2, 10 Gbps)

	External Ports	USB Type-C (24 pin) USB 3.1 (10Gbps)
Software	OS Compatibility	Windows 7, 8, 8.1, 10 Windows Server 2008 R2, 2012 R2, 2016, 2019 Mac OS X 10.9 to 10.10 Linux 3.5 to 4.14.x <i>LTS version only</i>
Special Notes / Requirements	System and Cable Requirements	PCI Express enabled computer or server with a PCI Express x4 slot or higher (x8, x16)
	System and Cable Requirements	Optional SATA power or LP4 Molex connector
	Note	The maximum throughput of this card is limited by the bus interface. PCI Express Gen 1.0 max throughput is 2.5Gbps per lane. PCI Express Gen 2.0 max throughput is 5Gbps per lane.
	Note	The available bandwidth (10Gbps) is shared equally between the two ports.
Environmental	Operating Temperature	0C to 60C (32F to 140F)
	Storage Temperature	-10C to 70C (14F to 158F)
	Humidity	5% ~ 90% RH
Physical Characteristics	Product Length	5.0 in [1.3 cm]
	Product Width	3.3 in [85.000 mm]
	Product Height	0.8 in [20.000 mm]
	Weight of Product	2.9 oz [81.000 g]
Packaging Information	Package Length	6.7 in [1.7 cm]
	Package Width	5.6 in [1.4 cm]
	Package Height	1.2 in [30.000 mm]
	Shipping (Package) Weight	4.7 oz [134.000 g]
What's in the Box	Included in Package	controller card
	Included in Package	instruction manual

**Product appearance and specifications are subject to change without notice.*

