

Dual Port Gigabit PCI Express Server Network Adapter Card - PCIe NIC

Product ID: ST1000SPEXD4



The ST1000SPEXD4 PCI Express Dual-Port Gigabit Network Card lets you add two gigabit Ethernet ports to a client, server or workstation through a single PCIe slot. Each port provides 10/100/1000 Mbps capable Ethernet and is fully compatible with IEEE 802.3/u/ab standards.

Suitable for any standard PCI Express-enabled system, the 2-port Ethernet card supports full-duplex flow control for maximum data transfer speeds of up to 2000 Mbps - an ideal 2-port NIC for setting up dual-homed, or multi-homed host configurations providing added security to corporate networks.

The dual-port server adapter is compliant with the PCIe 2.0 standard and features support for Jumbo Frames and 802.1q VLAN tagging as well as Wake on LAN (WoL). The adapter includes an optional low-profile / half-height bracket that can be used for installation into a standard or small form-factor computer chassis.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Ideal for VM environments with multiple operating systems, requiring shared or dedicated NICs
- Provide redundant connectivity to ensure an uninterrupted network connection
- Configure a dual-homed proxy or gateway system for an added layer of security
- Specially designed for desktop PC clients, servers, and workstations with few PCI Express slots available

Features

- Two 10/100/1000Mbps compatible RJ-45 Ethernet ports
- Compatible with PCI Express Base Specification 2.0 (backward compatible with 1.0a/1.1)
- Fully Compliant with IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, and supports IEEE 802.1Q VLAN tagging, IEEE 802.1P Layer 2 Priority Encoding and IEEE 802.3x Full Duplex Flow Control
- Supports Microsoft NDIS5 Checksum Offload (IP, TCP, UDP) and Large send Offload
- Wake-on-LAN / Remote Wake-up support
- Configured with standard profile bracket, low profile/half-height bracket included
- Supports Pair Swap / Polarity / Skew Correction
- Up to 9K Jumbo Frame support

Hardware

| | |
|--------------------|---|
| Warranty | 2 Years |
| Ports | 2 |
| Interface | RJ45 (Gigabit Ethernet) |
| Bus Type | PCI Express |
| Card Type | Standard Profile (LP bracket incl.) |
| Port Style | Integrated on Card |
| Industry Standards | IEEE 802.3, IEEE 802.3u, IEEE 802.3ab PCI Express Base Specification 2.0 |
| Chipset ID | Realtek - RTL8111H ASMedia - ASM1182E |

Performance

| | |
|----------------------------|--|
| Maximum Data Transfer Rate | 2000 Mbps (full-duplex), 1000 Mbps (half-duplex) |
| Compatible Networks | 10/100/1000 Mbps |
| Auto MDIX | Yes |
| Full Duplex Support | Yes |
| Jumbo Frame Support | 9K max. |



| | |
|---------------------|--|
| Promiscuous Mode | Yes |
| Supported Protocols | IEEE 802.1Q VLAN tagging, IEEE 802.1P Layer 2 Priority Encoding and IEEE 802.3x Full Duplex Flow Control |

Connector(s)

| | |
|-------------------|----------------|
| Connector Type(s) | PCI Express x1 |
| External Ports | RJ-45 |

Software

| | |
|------------------|--|
| OS Compatibility | Windows 2000, XP, Vista, 7, 8, 8.1, 10 Windows Server 2003, 2008 R2, 2012, 2012 R2, 2016, 2019 Mac OS 10.4 to 10.9 Linux 2.4.x to 4.11.x <i>LTS Versions only</i> |
|------------------|--|

Special Notes / Requirements

| | |
|-------------------------------|----------------------------|
| System and Cable Requirements | Available PCI Express slot |
|-------------------------------|----------------------------|

Indicators

| | |
|----------------|--|
| LED Indicators | Yellow - Gigabit Mode Green - Link/Activity |
|----------------|--|

Environmental

| | |
|-----------------------|--------------------------|
| Operating Temperature | 0C to 70C (32F to 158F) |
| Storage Temperature | 0C to 100C (32F to 212F) |
| Humidity | 10~90% RH |

Physical Characteristics

| | |
|-------------------|------------------|
| Material | Steel |
| Product Length | 3.6 in [92.6 mm] |
| Product Width | 0.7 in [18 mm] |
| Product Height | 4.7 in [12 cm] |
| Weight of Product | 1.9 oz [53 g] |

**Packaging
Information**

| | |
|------------------------------|------------------|
| Package Length | 5.6 in [14.3 cm] |
| Package Width | 6.7 in [17 cm] |
| Package Height | 1.2 in [30 mm] |
| Shipping (Package) Weight | 5.0 oz [142 g] |

**What's in the
Box**

| | |
|---------------------|---------------------|
| Included in Package | PCIe Network Card |
| | Low Profile Bracket |
| | Driver CD |
| | Instruction Manual |

****Product appearance and specifications are subject to change without notice.***

