

Wireless HDMI Extender, 4K 60Hz, Transmitter and Receiver Kit, Up to 165ft (50m), No Line-Of-Sight Required, IR Extension, Includes Mounting Kit

Product ID: ST121WHDS2



Connect the Transmitter Unit to an HDMI source and the Receiver Unit to an HDMI display to wirelessly transmit 4K 60Hz HDMI at distance of up to 165 feet (50 meters), using this Wireless HDMI Extender Kit.

This wireless HDMI extender eliminates the need for a separate ethernet cable between the transmitter and receiver, providing a clean and flexible setup. Operates with or without line of sight (LOS/NLOS), making it ideal for media closets and cabinets. Also, the transmitter features an HDMI output for connecting a local display, making it ideal for presentations and conferences. A 5GHz point-to-point connection between the transmitter and receiver avoids the more congested 2.4GHz wireless frequencies. Up to four paired extender kits can be used in the same area.

This wireless HDMI extender offers a straightforward, plug-and-play experience, eliminating the need for IP configurations, software installations, or driver setups, making it an accessible solution for various applications.

The included mounting kits enable versatile installation options for both the transmitter and receiver. An IR blaster and receiver are also included to extend infrared signals. Optional rubber feet are included for added stability and surface protection.

This extender supports HDMI 2.1 TMDS with 18Gbps bandwidth, HDCP 1.4/2.2, 2.1 channel audio, and Audio Return Channel (ARC). It uses a dual-antenna design for improved wireless performance. This wireless HDMI extender features 8kV air and 6kV contact electrostatic discharge (ESD) protection.

Certifications, Reports and Compatibility









Applications

- Connect to an HDMI source and display to wirelessly transmit 4K 60Hz HDMI w/2.1ch ARC
- Place the display in a convenient viewing area while the system equipment is located elsewhere in a clean and safe environment

Features

- HDMI OVER WIRELESS: Transmit 4K 60Hz HDMI signals wirelessly up to 165 feet (50 meters) in a point-to-point signal; No line-of-sight required for operation making it ideal for media closets/cabinets; No cable run ensures a clutter-free, rapid setup
- LOCAL HDMI PASS-THROUGH: Transmitter features an HDMI output (loop-out) to connect a local display; Ideal for presentation centers, boardrooms/meeting rooms, classrooms, trade shows, and conference centers
- NO DRIVERS OR SOFTWARE: No IP configuration, software, or drivers are required, ensuring a streamlined cable-free extension; 5GHz point-to-point connection from transmitter to receiver supports channel switching to avoid interference in busy environments
- INSTALLATION OPTIONS: Included mounting kit for transmitter/receiver provides versatile installation options; Up to 4 paired extender kits in one local area; IR Blaster/Receiver for IR extension; Rubber feet included for stability/surface protection
- TECHNICAL SPECIFICATIONS: HDMI 2.1 TMDS supporting 18Gbps bandwidth, HDCP 1.4/2.2, 2.1ch audio, and Audio Return Channel (ARC); 5GHz wireless dual-antenna design; 8kV air and 6kV contact level-3 ESD protection

Hardware		
	Warranty	2 Years
	Ports	1
	Cabling	Wireless Ethernet
	Audio	Yes
	Rack-Mountable	No
	Industry Standards	HDMI 2.1 (TMDS)
Performance		
	Max Distance	50m [164ft]





Maximum Digital Resolutions

4K 60Hz

Supported Resolutions

40962160 @ 30hz

3840 x 2160 @ 60hz

3840 x 2160 @ 30hz

2560 x 1600 @ 60hz

2560 x 1440 @ 60hz

2048 x 1536 @ 60hz

1920 x 1440 @ 60hz

1920 x 1200 @ 60hz

1920 x 1080 @ 60hz

1680 x 1050 @ 60hz

1600 x 1200 @ 60hz

1600 x 1024 @ 60hz

1600 x 900 @ 60hz

1366 x 768 @ 60hz

1360 x 768 @ 60hz

1360 x 765 @ 60hz

1280 x 1024 @ 60hz

1280 x 960 @ 60hz

1280 x 800 @ 60hz

1280 x 768 @ 60hz

1280 x 720 @ 60hz

1176 x 664 @ 60hz

1152 x 864 @ 60hz

1024 x 768 @ 60hz

800 x 600 @ 60hz

Other SDR resolutions may be supported

Wide Screen Supported Yes

Bandwidth 18Gbps

Audio Specifications HDMI - 2 Channel Audio



	Frequency	5.1 - 5.2 GHz
	General Specifications	HDCP 1.4/HDCP 2.2
Connector(s)	Local Unit Connectors	1 - HDMI
		1 - HDMI
		1 - USB Micro-B (5 pin)
		1 - 3.5mm Stereo Female 3 pos
		2 - SMA (Coax, SubMiniature A)
	Remote Unit Connectors	1 - HDMI
		1 - USB Micro-B (5 pin)
		1 - 3.5mm Stereo Female 3 pos
		2 - SMA (Coax, SubMiniature A)
Software	OS Compatibility	No Drivers or Software Required
Special Notes / Requirements		
Kequirements	Note	Transmission distances may vary based on the installation environment.
		Solid structures like walls, bricks, and glass can reduce or completely block signals.
		Up to four Wireless HDMI Extender Kits can be used in a single local area.
		The firmware update port is for manufacturer use only.
Indicators		
	LED Indicators	1 - Power Indicator
		Solid Blue: Unit is Receiving Power
		1 - Wireless Connection Indicator
		Solid Orange: Wireless Connection Established
		Quick Flash: Wireless Pairing Mode



Slow Flash: Waiting for Wireless Connection

1 - HDMI Signal Transmission Indicator

Solid Orange: HDMI Signal is transmitting

Quick Flash: Restoring to Default settings

Off: No HDMI Signal detected

Power

Power Source 2 AC Adapters Included

Environmental

Operating Temperature -20C to 60C (-4F to 140F)

Storage Temperature -30C to 70C (-22F to 158F)

Humidity 0% - 90% RH (non-condensing)

Physical Characteristics

Color Black

Material Metal

Product Length 4.9 in [12.5 cm]

Product Width 4.5 in [11.5 cm]

Product Height 0.8 in [2.1 cm]

Weight of Product 12.2 oz [346.0 g]

Packaging Information

Package Length 6.1 in [15.6 cm]

Package Width 14.1 in [35.8 cm]

Package Height 3.5 in [8.9 cm]

Shipping (Package)

Weight

3.0 lb [1.4 kg]

What's in the Box

Included in Package 1 - Wireless Transmitter

1 - Wireless Receiver



1 - IR Blaster

1 - IR Receiver

4 - Wireless Antenna

2 - Universal Power Adapter (NA/EU/UK)

2 - Mounting Kit

1 - Set of Rubber Feet

1 - Quick-Start Guide

Warranty Information

Warranty

2 Years

^{*}Product appearance and specifications are subject to change without notice.