

4 Port VGA Video Splitter - hochauflösend - 1 x VGA (Stecker) 4 x VGA (Buchse)

Produkt-ID: ST124PRO



The ST124PRO 4 Port High Resolution VGA Video Splitter - 350 MHz splits a VGA video source signal to 4 monitors or projectors simultaneously - a professional grade solution that is perfect for presentations, classrooms, tradeshows, or in-store displays, where the highest quality video on several monitors is needed.

This High Resolution VGA Splitter supports monitors with up to 350MHz of video bandwidth and display resolutions up to 2048x1536 @80Hz. For added versatility, the VGA splitter features an integrated booster circuit that allows the video signal to be extended up to 210 feet (65 meters), enabling you to situate your displays in the most convenient location based on your application.

This product is TAA compliant and backed by a Startech.com 2-year warranty with free lifetime technical support., Male to Female VGA extension cable required (MXT101HQ)

Zertifikate Berichte und Kompatibilität



Anwendungen

- Create engaging multimedia presentations for demonstration in lecture halls and classrooms
- Display travel schedules and alerts in airports, bus terminals and train stations etc.
- Create eye-catching displays in trade-shows and auditoriums

- Use for in-store product merchandising in retail environments to give your advertisements greater visibility
- Get your message across multiple displays for trade-shows or information booths/kiosks
- Quick and easy solution to split a video signal in an auditorium or house of worship

Merkmale

- Allows 1 VGA video source to simultaneously display on 4 different monitors
- Supports resolutions up to 2048x1536 @ 80Hz
- High video bandwidth (350 MHz)
- Daisy chainable for almost unlimited expansion
- Maximum VGA cable length of 210ft (65m)
- Uses standard monitor extension cables (See Accessories)
- DDC compatible

Hardware

Garantiebestimmungen	2 Years
Ports	4
Behördliche Genehmigungen	FCC Part 15 Class A, CE Mark
Industrienormen	DDC compatible - all other monitors must be able to support the highest video resolution of the DDC-type monitor connected to Video Out 1

Leistung

Max. Kabellänge	210.0 ft [64.0 m]
Max. Analogauflösungen	2048x1536 @ 80Hz
Bandbreite	350MHz
Allgemeine Spezifikationen	Male to Female VGA extension cable required (MXT101HQ)

MTBF 1.065.824 Stunden

Steckverbinder

Steckverbindertyp(en) 4 - VGA (15-polig, High Density D-Sub)
1 - VGA (15-polig, High Density D-Sub)

Strom

Stromversorgung Mit Netzadapter
Eingangsspannung 100 - 240 AC
Eingangsstrom 0.3 A
Ausgangsspannung 5 DC
Ausgangsstrom 1 A
Steckertyp N
Stromverbrauch 5

Umgebungsbedingungen

Betriebstemperatur 0 to 40 °C
Lagertemperatur 5 to 40 °C
Feuchtigkeit 0~80% RH non-condensing

Physische Eigenschaften

Farbe Schwarz
Gehäusotyp Stahl
Produktlänge 7.2 in [18.2 cm]
Produktbreite 3.1 in [8.0 cm]
Produkthöhe 0.8 in [2.1 cm]
Produktgewicht 13.8 oz [392.0 g]

Verpackungsinformationen

Paketmenge	1
Paketlänge	9.6 in [24.3 cm]
Paketbreite	7.3 in [18.6 cm]
Pakethöhe	3.7 in [9.5 cm]
Versandgewicht (Verpackung)	1.5 lb [0.7 kg]

Verpackungsinhalt

Im Paket enthalten	1 - 4 Port High Res. Video Splitter
	4 - Rubber Feet
	1 - Power Adapter
	1 - Instruction Manual

Garantieinformationen

Warranty	2 Jahre
----------	---------

* Größe, Aussehen und Spezifikationen sind Änderungen ohne vorherige Ankündigung vorbehalten.