


Dual Port PCI Express (PCIe x4) Gigabit Ethernet Server Adapter Network Card - Intel i350 NIC

Product ID: ST2000SPEXI



The ST2000SPEXI PCI Express Dual Port Gigabit Network Card lets you add two gigabit Ethernet ports to a desktop computer through a single, four-lane (x4 or higher)PCI Express slot. Each port is fully compatible with IEEE 802.3/u/ab standards, for 10/100/1000 Mbps auto-negotiation.

This 2-port GbE network card is based on the high-performance Intel I350 chipset, which offers several advanced driver options including IEEE 802.3ad link aggregation / teaming support, enabling you to add additional bandwidth to your system. Support for Jumbo Frames, full-duplex operation and 802.1q VLAN tagging also aid in creating an efficient network configuration.

Also useful for virtualization applications (check your VM software for chipset compatibility) or setting up a dual-homed host configuration, this dual-port network card lets you accommodate several complex network scenarios, to meet your business needs. For added versatility, the controller card is equipped with a standard profile bracket and includes a low-profile/half-height bracket for installation in small form-factor computers.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

## **Certifications, Reports and Compatibility**

## **Applications**

- Ideal for VM environments with multiple operating systems, requiring shared or dedicated NICs
- Provide redundant connectivity to ensure an uninterrupted network connection
- Configure a dual-homed proxy or gateway system for an added layer of security
- Specially designed for desktop PC clients, servers, and workstations with few PCI Express slots available



## **Features**

- Two 10/100/1000Mbps compatible RJ-45 Ethernet ports
- Jumbo Frame support up to 9k bytes
- Wake-on-LAN / Remote Wake-up support
- Configured with standard profile bracket, low profile/half-height bracket included
- Fully Compliant with IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3ad (link aggregation) and supports IEEE 802.1Q VLAN tagging
- Supports Checksum Offload (IP, TCP, UDP), Transmit Segmentation Offload (TCP, UDP) and Large send Offload
- Compatible with PCI Express Base Specification 2.1 (backward compatible with 1.0a/1.1)
- Four-lane (x4) PCI Express compatible with x4, x8 and x16 PCIe slots
- Supports Intel Virtualization Technology (VT-c, VMDq, SR-IOV)
- Teaming Support

| Hardware |                    |                                       |
|----------|--------------------|---------------------------------------|
|          | Warranty           | 2 Years                               |
|          | Ports              | 2                                     |
|          | Interface          | RJ45 (Gigabit Ethernet)               |
|          | Bus Type           | PCI Express                           |
|          | Card Type          | Standard Profile (LP bracket incl.)   |
|          | Port Style         | Integrated on Card                    |
|          | Industry Standards | PCI Express Base Specification 2.1    |
|          |                    | IEEE 802.3, IEEE 802.3u, IEEE 802.3ab |
|          | Chipset ID         | Intel - I350-AM2                      |
|          |                    |                                       |

## Performance

Maximum Data Transfer 2000 Mbps (full-duplex), 1000 Mbps (half-duplex) Rate

Compatible Networks 10/100/1000 Mbps

Auto MDIX Yes



Full Duplex Support Yes

Jumbo Frame Support 9K max.

Promiscuous Mode Yes

MTBF 432,400 hours

Supported Protocols IEEE 802.3ad (link aggregation), IEEE 1588 (time sync) / 802.1AS,

IEEE 802.1q (VLAN tagging)

Connector(s)

Connector Type(s) PCI Express x4

External Ports RJ-45

**Software** 

OS Compatibility Windows 7, 8, 8.1, 10

Windows Server 2008 R2, 2012, 2012 R2, 2016, 2019

Linux 2.4.x to 4.11.x <i>LTS versions only</i>

Special Notes / Requirements

System and Cable Requirements

Available PCI Express x4 or higher (x8, x16) slot

**Indicators** 

LED Indicators Link / Activity

10/100/1000 Mbps Indicator

**Environmental** 

Operating Temperature 0C to 50C (32F to 122F)

Storage Temperature -20C to 60C (-4F to 140F)

Humidity 5~85% RH

Physical Characteristics

Material Steel

Product Length 2.6 in [67 mm]

Product Width 0.7 in [19 mm]



|                          | Product Height               | 4.8 in [12.1 cm]    |
|--------------------------|------------------------------|---------------------|
|                          | Weight of Product            | 2.8 oz [80 g]       |
| Packaging<br>Information |                              |                     |
|                          | Package Length               | 5.7 in [14.4 cm]    |
|                          | Package Width                | 6.8 in [17.2 cm]    |
|                          | Package Height               | 1.1 in [29 mm]      |
|                          | Shipping (Package)<br>Weight | 5.8 oz [165 g]      |
| What's in the            |                              |                     |
|                          | Included in Package          | Driver CD           |
|                          |                              | Instruction Manual  |
|                          |                              | Low Profile Bracket |
|                          |                              | 2 Port Network Card |

<sup>\*</sup>Product appearance and specifications are subject to change without notice.