

## 32 Port Multi-user Cat5 Matrix IP KVM Switch

**Product ID:** SV3253DXI



The SV3253DXI 32 Port Enterprise class CAT 5 Matrix IP KVM Switch provides multi-user control of connected servers, devices and services connected through a local network infrastructure. Multi-user functionality allows 1 local user, 1 IP user and 1 remote console user (with a console extender device – SV5CONS not included) to simultaneously access 3 different systems connected to the KVM.

The IP KVM switch allows users to reboot the system, access the BIOS and have full control over the keyboard and mouse as if they are on site, saving time and resources by providing complete remote control of connected equipment.

Aside from a dependable and convenient operating platform, the SV3253DXI also provides features essential for secure and efficient management of mission- critical servers and devices - day in and day out.

How it works:

Connectivity Diagram

Note: The following interface modules are required for host connectivity

SV5USBM - USB Server Interface Module for the Enterprise Series IP KVMs

SV5PS2M - PS/2 Server Interface Module for the Enterprise Series IP KVMs

## Certifications, Reports and Compatibility

### Applications

- Users can reboot the system, access the BIOS, and have full control over the keyboard and mouse - as if they are on site

- Administer multiple servers for your Co-Location/ISP facility at the BIOS level either onsite or remotely saving time and money
- Create a scalable, streamlined access solution in your Datacenter or Server Farm
- Perfect for manufacturing line computer control, simplifying access to multiple systems
- Great for PC test/burn-in computer control saving the desk space required for multiple monitors, keyboards and mice
- Scale existing infrastructure, and access existing KVM analog switches via TCP/IP
- Remote access for outsourced server / IT hardware management, saving travel time
- Remote access to mission-critical corporate datacenter servers ensuring maximum uptime

## Features

- BIOS level control of the attached servers from anywhere over the internet
- Supports virtual media and file transferring for connected servers (with the use of the USB Interface Modules)
- Local hard drive can be connected to the KVM and used as a shared resource among all connected servers without affecting regular network traffic to file servers
- Longest supported distance from the server to the KVM compared to competitors (164 feet)
- Serial control via SSH and Telnet through the IP interface
- Secure access to the web console via user ID and SSL password
- Supports up to 32 user accounts and incorporates SSL encryption of session data, and SSL web communication encryption
- High resolution support for 1600 x 1200 @ 75Hz
- Supports a maximum resolution of 1600 x 1200 at 16 bit via the web interface
- Low Power consumption (as much as 25% lower than competitors)
- Versatile wide range power support, works with anything from 85-260 VAC
- Crash Cart ports on the front of the KVM for quick connections
- Plug and Play compliant hybrid KVM supporting both USB and PS2
- Web interface works with smartphone devices that support VNC or java for control while mobile
- Works with PC, Mac, Linux and Sun Systems
- Upgradeable firmware

- Each computer name can be defined via the OSD menu and Web interface
- Obtains an IP address using DHCP or manual configuration
- Made in North America

---

#### Hardware

Warranty	2 Years
Audio	No
KVM Ports	32
PC Interface	USB and PS/2
PC Video Type	VGA
Number of Monitors Supported	1
Rack-Mountable	Yes
Cables Included	No
Daisy-Chain	No

---


#### Performance

IP Control	Yes
Hot-Key Selection	Yes
Maximum Cable Length	164ft (50m)
Maximum Analog Resolutions	Standard(4:3) - 1600x1200 @60Hz (Recommended 1280x1024) Widescreen(16:9) - 1280x960
Maximum Number of Users	1 x Local, 1 x Remote Console, 1 x IP User - Total 3
Port Selection Support	Hotkeys and OSD (On Screen Display)
Security Features	IP Filtering
Supported Protocols	SSH, SSL, HTTP, SNMP, HTTPS, VNC VNCS, Radius

---

#### Connector(s)

Console Interface(s)	PS/2 (6 pin, Mini-DIN)
----------------------	------------------------



	RJ-45
	RJ-45
	RJ-45
	USB Type-A (4 pin) USB 2.0
	VGA (15 pin, High Density D-Sub)
Host Connectors	RJ-45

---

**Software**

OS Compatibility	OS independent; No software or drivers required
------------------	---

---

**Special Notes / Requirements**

Note	Source code for the unit operating system is available upon request. Please contact us by phone, live chat, or email to make your request. This offer is valid for three years from the date of purchase and/or for as long as parts or customer support is offered for this product. Charges for the reasonable cost of copying and/or conveying may apply.
------	--

---

**Indicators**

LED Indicators	Power
	Link

---

**Power**

Power Source	AC Adapter Included
Input Voltage	115V-230V AC

---

**Environmental**

Operating Temperature	0C to 40C (32F to 104F)
Storage Temperature	-40C to 65C (-40F to 158F)
Humidity	80% RH

---

**Physical Characteristics**

Color	Black
Material	Aluminum
Product Width	17.3 in [44 cm]



Product Height	1.7 in [44 mm]
Product Depth	12.2 in [31 cm]
Weight of Product	4.9 lb [2.2 kg]

---

**Packaging Information**

Package Length	22.6 in [57.4 cm]
Package Width	4.1 in [10.5 cm]
Package Height	14.7 in [37.4 cm]
Shipping (Package) Weight	6.6 lb [3.0 kg]

---

**What's in the Box**

Included in Package	32 Port IP KVM Switch
	Mounting Hardware
	Bag, Screws
	Power Cable
	Instruction Manual

---

*\*Product appearance and specifications are subject to change without notice.*

