

USB to HDMI External Dual or Multi Monitor Video Adapter with Audio

Product ID: USB2HDMI



The USB2HDMI USB to HDMI External Video Adapter (Dual or Multi Monitor with Audio) turns an available USB 2.0 port into an HDMI output, with high resolution video support (up to 1920x1080) and audio.

The USB HDMI adapter can be used to mirror your primary desktop, showing the same image on each display, or to extend your desktop to double your workspace and increase your productivity. This external graphics card is a cost-saving multi-monitor or dual display solution, for either laptop or desktop applications, offering the ability to connect an additional HDMI (or DVI) enabled display to your computer setup without the hassle of opening the computer case to install a new video card.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.



Certifications, Reports and Compatibility

Applications

• Add a secondary display adapter and extend your desktop display without taking apart your computer to install a new video card

• Connect multiple monitors to a single computer, to create engaging multimedia presentations



• Use the adapter to connect your PC to your television for showing family pictures and movies

• Great for researchers and writers offering the ability to have reference material on one display and a working document copy on the other

• Increase productivity by running multiple applications on different screens, check your email on one display and search the web on the other

· View large or multiple spreadsheets across multiple displays

• A compact, lightweight solution for traveling business associates using laptop PCs, enabling connection to a secondary display/projector

Features

- Supports resolutions up to 1920x1080
- · Quick and easy installation
- USB-powered No external power adapter required
- Choose between Mirrored, Extended or Primary display configurations
- Driver software supports display rotation
- Supports the Windows Aero interface
- Supports 2-channel (Stereo) audio

Hardware		
	Warranty	2 Years
	AV Input	USB 2.0
	AV Output	HDMI
	Audio	Yes
	USB Pass-Through	No
	Memory	16MB
	Chipset ID	DisplayLink - DL-165

Performance

Maximum Digital Resolutions

1920x1080



	Supported Resolutions	Widescreen (16/32 bit):
		1920x1080, 1680x1050, 1440x900, 1440x480, 1280x800, 1280x720
		Standard (16/32 bit):
		1600x1200, 1400x1050, 1280x1024, 1280x960, 1152x864, 1024x768, 800x600, 720x480, 640x480
	Wide Screen Supported	Yes
Connector(s)		
	Connector A	1 - USB Mini-B (5 pin)
	Connector B	1 - HDMI (19 pin)
Software		
	OS Compatibility	Windows 2000/ XP(32bit)/ Vista(32/64bit)/ 7(32/64bit) / 8(32/64bit) *, Aero 3D interface supported
		macOS Sequoia (15.0), macOS Sonoma (14.0), macOS Ventura (13.0), Monterey (12.0), Big Sur (11.0) / X Mountain Lion (10.8) / Lion (10.7) / Snow Leopard (10.6) / Leopard (10.5) / Tiger (10.4)
	Microsoft WHQL Certified	Yes
		Tes
Special Notes / Requirements		Tes
	System and Cable	System Processor: 1.2GHz
	System and Cable	System Processor: 1.2GHz
	System and Cable Requirements	System Processor: 1.2GHz System Memory: 512MB This USB video adapter uses a DisplayLink family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, avoid using devices
	System and Cable Requirements	System Processor: 1.2GHz System Memory: 512MB This USB video adapter uses a DisplayLink family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, avoid using devices with different family chipsets, such as Trigger or Fresco Logic Connect a maximum of five USB video adapters on a single computer. Support for multiple adapters will vary depending
	System and Cable Requirements	System Processor: 1.2GHz System Memory: 512MB This USB video adapter uses a DisplayLink family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, avoid using devices with different family chipsets, such as Trigger or Fresco Logic Connect a maximum of five USB video adapters on a single computer. Support for multiple adapters will vary depending upon your system resources This USB video adapter is not intended for graphical intensive
Requirements	System and Cable Requirements	System Processor: 1.2GHz System Memory: 512MB This USB video adapter uses a DisplayLink family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, avoid using devices with different family chipsets, such as Trigger or Fresco Logic Connect a maximum of five USB video adapters on a single computer. Support for multiple adapters will vary depending upon your system resources This USB video adapter is not intended for graphical intensive
Requirements	System and Cable Requirements Note	System Processor: 1.2GHz System Memory: 512MB This USB video adapter uses a DisplayLink family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, avoid using devices with different family chipsets, such as Trigger or Fresco Logic Connect a maximum of five USB video adapters on a single computer. Support for multiple adapters will vary depending upon your system resources This USB video adapter is not intended for graphical intensive applications, such as gaming



Physical Characteristics		
	Color	Black
	Material	Plastic
	Product Length	4.3 in [10.9 cm]
	Product Width	2.0 in [5.2 cm]
	Product Height	0.7 in [1.9 cm]
	Weight of Product	10.6 oz [300 g]
Packaging Information		
	Package Length	9.0 in [22.9 cm]
	Package Width	6.0 in [15.3 cm]
	Package Height	2.5 in [63 mm]
	Shipping (Package) Weight	0.9 lb [0.4 kg]
What's in the Box		
	Included in Package	1 - USB2HDMI
		1 - USB A to mini B cable
		1 - Driver CD
		1 - Installation guide

*Product appearance and specifications are subject to change without notice.