

USB 3.0 to DisplayPort Adapter - 2560x1600

Product ID: USB32DPPRO



The USB32DPPRO USB 3.0 to DisplayPort Multi Monitor Adapter functions as an external DisplayPort video card, turning an available USB 3.0 port into a DisplayPort output, with support for high resolution 2560x1600 video, and 5.1 surround sound audio. The USB 3.0 DisplayPort adapter delivers a convenient, high-performance external video solution that makes it easy to add multi-monitor capability to a USB 3.0-enabled desktop or laptop computer (optimal performance from USB 3.0, backward compatible with USB 2.0).

Leveraging the high-bandwidth (5 Gbps) SuperSpeed USB 3.0 interface, the adapter delivers smooth, high-definition content to your DisplayPort-capable display, and can be used to mirror your primary desktop, showing the same image on each display, or to extend your desktop to double your workspace and increase your productivity.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.Recommended System Requirements:

CPU: Quad Core 2.4GHz or Higher (i5 recommended)

RAM: 4GB or higher

Certifications, Reports and Compatibility

Applications

- Add a secondary DisplayPort display and extend your desktop, without taking apart your computer to install a new video card
- Add multi-monitor capability to a single computer, to enhance multimedia presentations
- Great for researchers and writers, offering the ability to have reference material on one display while working on a separate document on another

- Increase productivity by running multiple applications on different screens - check your email on one display and search the web on the other
- View large or several spreadsheets across multiple displays
- A compact, lightweight solution for traveling business associates using USB 3.0-capable laptop PCs, enabling connection to a secondary display/projector

Features


- SuperSpeed USB 3.0 (5 Gbps) Interface, backward compatible with USB 2.0
- Supports resolutions up to 2560x1600
- DisplayLink 4K Plug-and-Display certified - automatic driver installation and updates
- USB-powered - No external power adapter required
- Choose between Mirrored, Extended or Primary display configurations
- Driver software supports display rotation
- Supports the Windows Aero interface
- Supports 5.1 channel audio
- Supports the use of multiple USB32DPPRO USB 3.0 DisplayPort adapters on a single system (up to 5)

Hardware

Warranty	2 Years
AV Input	USB 3.0
AV Output	DisplayPort
Audio	Yes
USB Pass-Through	No
Memory	64MB
Industry Standards	Standard DisplayPort, SuperSpeed USB 3.0, USB 2.0
Chipset ID	DisplayLink - DL-3500

Performance

Maximum Digital Resolutions	2560x1600
-----------------------------	-----------



Supported Resolutions	<p>Widescreen(16/32 bit):</p> <p>2560x1600, 2560x1440, 2048x1152, 1920x1200, 1920x1080, 1680x1050, 1600x900, 1440x900, 1360x768, 1280x800, 1280x768, 1280x720</p> <p>Standard(16/32 bit):</p> <p>1600x1200, 1400x1050, 1280x1024, 1280x960, 1152x864, 1024x768, 800x600</p>
Wide Screen Supported	Yes
Audio Specifications	5.1-Channel Surround (48Khz)
General Specifications	<p>Note: If using OS X 10.8, Apple update 10.8.3 must be installed before installing DisplayLink software. 10.8.3 fixes several serious OS X bugs exposed when DisplayLink software is installed.</p> <p>This USB video adapter uses a DisplayLink family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, please avoid using devices with a Trigger or Fresco family chipset.</p>

Connector(s)

Connector A	USB Type-A (9 pin) USB 3.0 (5 Gbps)
Connector B	DisplayPort (20 pin)

Software

OS Compatibility	<p>Windows 2000, XP, Vista, 7, 8, 8.1, 10</p> <p>macOS 10.6 to 10.12, 10.14 - 10.15, 11.0</p> <p>Ubuntu 14.04, 16.04, 18.04</p> <p>Chrome OS v55+</p>
------------------	---

Special Notes / Requirements

System and Cable Requirements	<p>System Processor: Quad Core 2.4GHz (i5 recommended)</p> <p>System Memory: 4GB</p>
Note	<p>This USB video adapter uses a DisplayLink family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, avoid using devices with different family chipsets, such as Trigger or Fresco Logic</p> <p>Connect a maximum of five USB video adapters on a single computer. Support for multiple adapters will vary depending upon your system</p>

resources

This USB video adapter is not intended for graphical intensive applications, such as gaming

Power

Power Source	USB-Powered
--------------	-------------

Environmental

Operating Temperature	0C to 35C (32F to 95F)
Storage Temperature	-5C to 40C (23F to 104F)
Humidity	20C to 80C (68F to 176F)

Physical Characteristics

Color	Black
Material	Plastic
Product Length	3.2 in [81.0 mm]
Product Width	1.0 in [26.0 mm]
Product Height	0.4 in [11.0 mm]
Weight of Product	0.6 oz [18.0 g]

Packaging Information

Package Length	5.9 in [14.9 cm]
Package Width	8.1 in [20.6 cm]
Package Height	1.5 in [39.0 mm]
Shipping (Package) Weight	6.2 oz [177.0 g]

What's in the Box

Included in Package	USB 3.0 to Displayport adapter
	USB cable (39.25 inches)
	driver CD
	installation guide



****Product appearance and specifications are subject to change without notice.***

