

USB 3.0 to HDMI External Multi Monitor Graphics Adapter with 3-Port USB Hub – HDMI and USB 3.0 Mini Dock – 1920x1200 / 1080p

Product ID: USB32HDEH3



The USB32HDEH3 USB 3.0 to HDMI Adapter turns a USB 3.0 port into an HDMI output port with 1920x1200/1080p video support. The adapter features a built-in 3-port USB 3.0 hub, which enables you to connect three different USB devices, along with the display adapter, to the same USB 3.0 port – an ideal workaround for Ultrabook or laptop computers that have a limited number of USB ports available.

Functioning as an external graphics card with audio support, this USB to HDMI adapter provides a convenient way to add multi-monitor capability to a USB 3.0-enabled desktop or laptop computer. Leveraging the high-bandwidth (5 Gbps) USB 3.0 interface, the adapter delivers smooth, high-definition content to your HDMI display / projector. The adapter can be used to mirror your primary desktop, showing the same image on each display, or to extend your desktop to double your workspace and increase your productivity.

The USB32HDEH3 also features a built-in 3-port USB 3.0 hub, which lets you use the device as a mini dock for connecting peripherals such as a mouse, printer and keyboard along with your monitor. Then, it's as easy as connecting your laptop to the adapter to sync each device at your work station – a versatile solution for making your laptop portable when you want it to be, and powerful when you need it to be.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Recommended System Requirements:

CPU: Quad Core 2.4GHz or Higher (i5 recommended)

RAM: 4GB or higher

Available USB 3.0 port

Certifications, Reports and Compatibility





Applications

Add an extra display and 3 additional USB devices to an Ultrabook or laptop computer with limited USB and video output ports

- Add a secondary HDMI display and extend your desktop
- Add multi-monitor capability to a single computer, to create engaging multimedia presentations
- Run multiple applications on different screens check your email on one display and search the web on the other
- Simultaneously view large or multiple spreadsheets across several displays
- Connect your PC to your HDMI-equipped projector or display for viewing family pictures and movies

• Great for boosting productivity for researchers and writers, offering the ability to have reference material on one display and a working document copy on the other

Features

- Built in 3-Port USB 3.0 hub offers improved connectivity options on your slimline laptop or Ultrabook
- High-bandwidth USB 3.0 host connection, for reliable high-definition video playback
- Choose between Mirrored, Extended or Primary display configurations
- Fast, easy installation
- USB-powered No external power adapter required
- Driver software supports display rotation





	Audio	Yes
	USB Pass-Through	Yes
	Memory	32MB
	Industry Standards	SuperSpeed USB 3.0, USB 2.0
	Chipset ID	Trigger - T5-302
Performance		
	Maximum Analog Resolutions	1920x1200
	Supported Resolutions	Widescreen(16/32 bit):
		1920x1200, 1920x1080, 1680x1050, 1600x900, 1440x900, 1360x768, 1280x800, 1280x768, 1280x720
		Standard(16/32 bit):
		1600x1200, 1400x1050, 1280x1024, 1280x960, 1152x864, 1024x768, 800x600
	Wide Screen Supported	Yes
	General Specifications	This USB video adapter uses a Trigger family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, please avoid using devices with a DisplayLink or Fresco family chipset.
Connector(s)		
	Connector A	1 - USB Type-A (9 pin, 5 Gbps)
	Connector B	1 - HDMI (19 pin)
		1 - USB Type-A (9 pin, 5 Gbps)
Software		
	OS Compatibility	Windows 11
		Windows 10 (32/64)
		Windows 8 / 8.1 (32/64)
		Windows 7(32/64)
		Windows Vista (32/64)
		Windows XP (32/64)



Special Notes / Requirements		
nequirements	System and Cable	System Processor: Quad Core 2.4GHz (i5 recommended)
	Requirements Note	System Memory: 4GB This USB video adapter uses a Trigger family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, avoid using devices with different family chipsets, such as DisplayLink or Fresco Logic
		Connect a maximum of five USB video adapters on a single computer. Support for multiple adapters will vary depending upon your system resources
		This USB video adapter is not intended for graphical intensive applications, such as gaming
Power		
	Power Source	Not Included (not required for standard applications)
	Input Voltage	5 DC
	Plug Type	н
Environmental		
	Operating Temperature	0C to 50C (32F to 122F)
	Storage Temperature	-10C to 75C (14F to 167F)
	Humidity	< 85% non-condensing
Physical Characteristics		
	Color	Black
	Material	Plastic
	Cable Length	5.7 in [146 mm]
	Product Length	9.3 in [23.5 cm]
	Product Width	1.7 in [4.4 cm]
	Product Height	0.6 in [1.4 cm]
	Weight of Product	2.2 oz [63 g]

Microsoft WHQL Certified Yes





Packaging Information

mormation	Package Quantity	1
	Package Length	8.3 in [21 cm]
	Package Width	5.7 in [14.5 cm]
	Package Height	1.5 in [38 mm]
	Shipping (Package) Weight	7.5 oz [212 g]
What's in the Box		
	Included in Package	1 - USB 3.0 to HDMI Adapter w/ 3-Port USB 3.0 Hub
		1 - Software Installation Disc
		1 - Instruction Manual

*Product appearance and specifications are subject to change without notice.

