

Dual-Monitor KVM USB 3.0 Docking Station for Two Laptops

Product ID: USB3DDOCKFT



This TAA compliant KVM USB 3.0 docking station for two laptops functions like a KVM switch, enabling you to share your keyboard, video, and mouse, and transfer files between your docked laptops.

Connect two laptops to this dock to share dual monitors, a keyboard, mouse, and peripherals. This KVM docking station lets you control two laptops and share two monitors and several peripherals between them while they're docked. The docking station features:

- 2 x monitor ports (DP and HDMI)*
- 5 x USB 3.0 ports
- 1 x Gigabit Ethernet port
- 1 x headset port

Instead of transferring files to the cloud or external storage, the docking station lets you quickly and securely transfer data between your docked laptops, using Windows Easy Transfer or the included PCLinq software.

The USB 3.0 dock's always-on USB fast-charge port lets you charge your tablets and other mobile devices, even if your laptops aren't docked.

This USB docking station gives you the option to connect a single 4K display instead of dual displays. Set your laptop workstation up with dual monitors (1x DisplayPort, 1x HDMI), or for higher resolutions, connect either a single HDMI or 4K DisplayPort monitor.

*Lower resolutions are also supported. For example, if the max is 3840 x 2160p (4K), it also supports 2560 x 1600p and 2560 x 1440p.

Compatible with Mac and Windows USB 3.0 equipped laptops, the KVM docking station includes two USB 3.0 cables for quick installation and features an easy-access button for easy switching between laptops.

StarTech.com laptop docking stations offer cost savings and faster deployment with just a single cable. This USB 3.0 Docking Station is backed by a competitive 3-year warranty and free lifetime Technical Support.

Certifications, Reports and Compatibility



Applications

- Classrooms
- Network and Systems Administration
- Computer Labs

Features

- Speed up your workflow with file sharing between host computers
- Set up easily with the included file sharing software and two USB 3.0 cables
- Charge your devices without a laptop connection using the always-on USB fast-charge port
- Control up to two host laptops using one dual-monitor workstation

Hardware	Warranty	3 Years
	4K Support	Yes
	Fast-Charge Port(s)	Yes
	Displays Supported	2
	Bus Type	USB 3.0
	Industry Standards	USB Battery Charging Specification Rev. 1.2
	Chipset ID	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab USB 3.0 - Backward compatible with USB 2.0/1.1 DisplayLink - DL-5900 VIA/VLI - VL812
Performance	Maximum Data Transfer Rate	5 Gbps (USB 3.0) 2 Gbps (Ethernet; Full-Duplex)
	Maximum Digital Resolutions	3840 x 2160 @ 30Hz (DisplayPort - Single Display)
	Type and Rate	
	UASP Support	2560 x 1440 (HDMI - Single Display)
	Compatible Networks	
	Auto MDIX	2048 x 1152 and 2048 x 1152 (DisplayPort and HDMI - Two Displays)

Full Duplex Support

Lower resolutions are also supported. For example, if the max is 3840 x 2160p (4K), it also supports 2560 x 1600p and 2560 x 1440p.

USB 3.0 - 5 Gbit/s

Yes

10/100/1000 Mbps

Yes

Yes

Connector(s)	Connector Type(s)	DisplayPort (20 pin)
	Connector Type(s)	HDMI (19 pin)
	Connector Type(s)	USB 3.0 A (Fast-Charge, 9 pin)
	Connector Type(s)	USB Type-A (9 pin) USB 3.0 (5 Gbps)
	Connector Type(s)	RJ-45
	Connector Type(s)	3.5 mm Mini-Jack (4 Position)
	Connector Type(s)	USB Type-B (9 pin) USB 3.0
	Connector Type(s)	Security Lock Slot
Software	OS Compatibility	Windows 7, 8, 8.1, 10
		macOS 10.8 - 10.12, 10.14 - 10.15
		Chrome OS v55+
Special Notes / Requirements	System and Cable Requirements	Two USB-enabled computers with an available USB 3.0 port on each computer (host)
	Note	USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to 5Gbps
	Note	If connected to a USB 2.0 host port, or if using a USB 2.0 host connection cable, performance may be limited (USB 3.0 host cables included)
	Note	A 4K-capable DisplayPort display is required to achieve 4Kx2K resolutions
	Note	PCLInq can be used in any operating system that the dock supports. Windows Easy Transfer can only be used in Windows 8.1, 8, and 7
Indicators	LED Indicators	Link (Green)
	LED Indicators	Activity (Amber)



Power	Power Source	AC Adapter Included
	Input Voltage	100 - 240 AC
	Input Current	1.5 A
	Output Voltage	5 DC
	Output Current	6.5 A
	Center Tip Polarity	Positive
	Plug Type	N
	Power Consumption (In Watts)	32.5
Environmental	Operating Temperature	0C to 40C (32F to 104F)
	Storage Temperature	-10C to 80C (14F to 176F)
	Humidity	0~90% RH
Physical Characteristics	Color	Black & Silver
	Material	Plastic
	Product Length	10.6 in [2.7 cm]
	Product Width	3.2 in [82 mm]
	Product Height	1.3 in [34 mm]
	Weight of Product	13.2 oz [374 g]
Packaging Information	Package Length	11.7 in [3.0 cm]
	Package Width	6.4 in [1.6 cm]
	Package Height	2.8 in [70 mm]
	Shipping (Package) Weight	2.5 lb [1.1 kg]
What's in the Box	Included in Package	3.3 ft [1 m] USB 3.0 host cables
	Included in Package	universal power adapter (NA/JP, EU, UK, ANZ)
	Included in Package	instruction manual
	Included in Package	laptop docking station

****Product appearance and specifications are subject to change without notice.***