

## Travel Docking Station for Laptops - VGA - USB 3.0

**Product ID:** USB3SMDOCKV



This travel docking station lets you turn your laptop into a mobile workstation. It's a travel-friendly solution that helps you connect extra devices to any computer, even when you're on the move.

With a lightweight design, this compact laptop docking station tucks neatly into your travel bag. Now, you can avoid the nuisance of carrying multiple adapters, by consolidating three essential connection ports into one convenient device.

Plus, the portable docking station complements your Ultrabook nicely, with an aesthetically matching black and silver housing.

Providing added distance flexibility via an integrated extended-length (21") USB 3.0 host cable, you can easily connect a VGA monitor as a second display.

The versatile docking station also adds Gigabit Ethernet and a USB 3.0 port to your laptop, letting you set up a multi-functional workstation on the run. Plus, you don't have to worry about sacrificing one of your laptop USB ports.

To save you time, setup is seamless and hassle-free. The travel dock automatically downloads the latest driver when connected to a Windows system with an active network connection.

The universal travel docking station for laptops works with almost any USB 3.0 capable system. It's USB-powered too, so you can get up and running without the aggravation of searching for an available power outlet.

The USB3SMDOCKV is backed by a StarTech.com 3-year warranty and free lifetime technical support.

## Certifications, Reports and Compatibility

### Applications

- Work from your Ultrabook or laptop easily, while you're on the run or on the road, by adding essential connectivity options
- Use your laptop as a multi-display workstation, through external monitor support
- Connect to your VGA-equipped projector and display multimedia content in boardrooms
- Connect your laptop to a wired Gigabit network in situations where a WiFi connection isn't available, such as in classrooms, offices, and hotels

## Features

- VGA video, USB 3.0 hub port, and GbE through a single USB 3.0 cable
- Compact and lightweight for maximum portability — multiple connection options in a travel-friendly casing
- Built-in, extended-length USB 3.0 cable for convenience and distance flexibility
- USB bus-powered - No external power adapter required (optional auxiliary USB power cable included)
- Hassle-free setup - Latest drivers are automatically downloaded in Windows systems when an active network connection is present
- IEEE 802.3, 802.3u and 802.3ab (10BASE-T, 100BASE-TX, and 1000BASE-T) compatible
- SuperSpeed USB 3.0 (5 Gbps) interface, backward compatible with USB 2.0
- Support for resolutions up to 2048x1152 (QWXGA)
- Choose between Mirrored, Extended or Primary display configurations

---

### Hardware

Warranty	3 Years
4K Support	No
Fast-Charge Port(s)	No
Displays Supported	1
Bus Type	USB 3.0
Industry Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab USB 3.0 - Hub port supports USB 2.0/1.1 backward-compatibility
Chipset ID	DisplayLink - DL-3700

---

### Performance

Maximum Data Transfer	5 Gbps (USB 3.0) <br / >2 Gbps (Ethernet; Full-Duplex)
-----------------------	--------------------------------------------------------

Rate	
Maximum Analog Resolutions	2048x1152 (VGA)
Type and Rate	USB 3.0 - 5 Gbit/s
UASP Support	Yes
Compatible Networks	10/100/1000 Mbps
Auto MDIX	Yes
Full Duplex Support	Yes

---

#### Connector(s)

Connector Type(s)	USB Type-A (9 pin) USB 3.0 (5 Gbps)
	VGA (15 pin, High Density D-Sub)
	RJ-45
	USB Type-A (9 pin) USB 3.0 (5 Gbps)
	USB Micro-B (5 pin)

---

#### Software

OS Compatibility	Windows XP SP3 (32-bit), Vista, 7, 8, 8.1, 10 macOS 10.6 to 10.12, 11.0
------------------	----------------------------------------------------------------------------

---

#### Special Notes / Requirements

System and Cable Requirements	USB enabled computer system with available USB 3.0 port
Note	Micro USB Port (Auxiliary Power Input Port)  If necessary the provided USB power cable may be connected to draw additional power from the host computer in order to sufficiently power all outputs simultaneously


---

#### Indicators

LED Indicators	Power
	Link/Activity
	Link

---

#### Power



Power Source                      USB-Powered

**Environmental**

Operating Temperature      0C to 50C (32F to 122F)

Storage Temperature        -20C to 60C (-4F to 140F)

Humidity                         5~85% RH

**Physical Characteristics**

Color                                Black & Silver

Material                            Plastic

Cable Length                    21.0 in [53.4 cm]

Product Length                4.2 in [10.6 cm]

Product Width                 2.7 in [68 mm]

Product Height                 1.0 in [25 mm]

Weight of Product             4.4 oz [126 g]

**Packaging Information**

Package Length                5.7 in [14.4 cm]

Package Width                 8.1 in [20.7 cm]

Package Height                1.9 in [47 mm]

Shipping (Package) Weight   9.2 oz [260 g]

**What's in the Box**

Included in Package            USB 3.0 Mini Docking Station

                                          USB Power Cable

                                          Driver CD

                                          Instruction Manual

*\*Product appearance and specifications are subject to change without notice.*

