

1ft (30cm) Heavy Duty Power Cord, Twist-Lock NEMA L5-15P to NEMA 5-15R Black Adapter Cord, 15A 125V, 14AWG, Heavy Gauge Plug Converter Cable, TAA Compliant, UL Listed

**Product ID:** W31C-4100-POWER-CORD



The IT Pro's Choice

StarTech.com's power cables are designed by IT professionals. We design our products to meet the technical requirements of wide variety of applications. Our in-house specialists subject our products to multiple rounds of comprehensive testing, designed to emulate real-world operational conditions. Third-party labs test our products to confirm compliance with the latest safety standards.

StarTech.com manufactures standard and heavy-duty power cords, extension cords, medical-grade cords, power splitter cables, and power cords featuring passthrough outlets. These products are produced in various lengths, with a range of connector ends, jacket types, and wire gauges. Our power cable products are chosen by IT professionals worldwide for the following reasons:.

- Certified for performance and safety - Manufactured using UL listed components to meet UL62 and UL817 compliance standards
- Reduced environmental impact and safe disposal by adhering to the rules, regulations, and directives stipulated by REACH and RoHS
- 100% Copper wiring tested for continuity and conductivity, ensuring maximum performance and reliability
- Temperature chamber tested to ensure reliable performance across a range of environmental conditions

Backed for life by StarTech.com, our brand is trusted throughout the IT ecosystem and used by over 80% of Fortune 500 companies.

## Certifications, Reports and Compatibility



## Applications

- Heavy Duty power cord supports high-powered equipment and PDUs
- Extend a server or rackmount equipment power cord by an additional 2ft

## Features

- **HEAVY DUTY ADAPTER CABLE:** 1ft (30cm) Adapter Power Cable with Twist-Lock NEMA L5-15P to NEMA 5-15R connector works with servers or high-power equipment; Locking L5-15 plug securely attaches to an outlet or power source; Indoor use; Rated up to 125V at 20A
- **BUILT FOR PERFORMANCE AND SAFETY:** UL Listed; VW-1 Fire Rated cable with fully molded connector strain reliefs for durability; 3-conductor power cable made with 100% copper wire
- **SPECS:** 1ft (30cm); TAA Compliant; Twist-Lock NEMA L5-15P to NEMA 5-15R; 14AWG; 125V 15A (Max); Jacket Rating: SJT; Color: Black; Temperature Range: -4F to 221F (-20 to 105); Cable O.D.: 0.36in (9.3mm)
- **COMPATIBILITY:** NEMA L5-15P to NEMA 5-15R power cord works with North American PDUs and high-powered devices; Convert a NEMA L5-15 outlet to 5-15R for convenient integration with servers, switches, or UPS; Heavy duty adapter power cord
- **THE IT PRO'S CHOICE:** Designed and built for IT Professionals, the heavy duty adapter power cord is backed for life, including free lifetime 24/5 multi-lingual technical assistance; This adapter power cable is available in other plug configurations

---

### Hardware

Warranty	Lifetime
Number of Conductors	3
Connector Plating	Nickel
Cable Jacket Material	PVC
Fire Rating	VW-1 Rated
Cable Type	SJT

---

### Performance

Maximum Cable Length	1.0 ft [0.3 m]
----------------------	----------------

---

### Connector(s)

Connector A	1 - NEMA L5-20P (North America)
Connector B	1 - NEMA 5-15 Power (North America)

---

**Power**

Output Current	15A
----------------	-----

---

**Environmental**

Operating Temperature	-20 to 105C (-4 to 221F)
Storage Temperature	-20 to 105C (-4 to 221F)
Humidity	0% to 65% RH

---

**Physical Characteristics**

Color	Black
Wire Gauge	14 AWG
Cable Length	1.0 ft [0.3 m]
Cable OD	0.4 in [9.3 mm]
Product Length	12.0 in [30.5 cm]
Product Width	1.5 in [3.9 cm]
Product Height	1.5 in [3.9 cm]
Weight of Product	0.0 oz [0.0 g]

---

**Packaging Information**

Package Length	5.7 in [14.5 cm]
Package Width	11.5 in [29.3 cm]
Package Height	1.6 in [4.0 cm]
Shipping (Package) Weight	6.0 oz [170.0 g]

---

**What's in the Box**

Included in Package	1 - 1ft NEMA 5-15R to NEMA L5-15P Heavy-Duty Power Cord
---------------------	---

---

*\*Product appearance and specifications are subject to change without notice.*